THE COMPLEXITY OF ORDER-COMPUTABLE SETS

HUISHAN WU

Abstract. This paper studies the conjecture of Hirschfeldt, Miller, and Podzorov in [13] on the complexity of order-computable sets, where a set A is order-computable if there is a computable copy of the structure $(\mathbb{N}, <, A)$ in the language of linear orders together with a unary predicate. The class of order-computable sets forms a subclass of Δ^0_2 sets. Firstly, we study the complexity of computably enumerable (c.e.) order-computable sets and prove that the index set of c.e. order-computable sets is Σ^0_4-complete. Secondly, as a corollary of the main result on c.e. order-computable sets, we obtain that the index set of general order computable sets is Σ^0_4-complete within the index set of Δ^0_2 sets. Finally, we continue to study the complexity of more general Δ^0_2 sets and prove that the index set of Δ^0_2 sets is Π^0_3-complete.

§1. Introduction. Computability theory is a useful tool to classify mathematical structures according to their intrinsic complexity. For the work on computable model theory, refer to books, e.g., Ash and Knight [1], Harizanov [11, Section 5]. For the work on special algebraic structures such as abelian groups, rings and fields, see, for instance, [2–4, 8–10, 12, 14, 15]. In [14], Lempp showed that the complexity of the problem of being torsion-free for a finitely presented group is Π^0_2-complete. Downey and Melnikov proved in [9] that a computable completely decomposable group is Δ^0_5-categorical; that is, any two computable presentations of such a group is isomorphic through a Δ^0_5-isomorphism. Riggs investigated the decomposability problem for torsion-free abelian groups in [17]; he obtained that the decomposability problem for torsion-free abelian groups of finite rank is Σ^0_3-complete, however, the same problem for general torsion-free abelian groups is Σ^1_1-complete. Conidis investigated the complexity of radicals of computable rings and of computable modules in [5, 6]; for instance, he constructed a computable noncommutative ring whose prime radical is Π^1_1-complete in [5]. Recently, we studied the complexity of decomposability of computable rings in [20] and obtained that the index set of computable decomposable rings is Σ^0_2-complete within the index set of computable rings.

In [13], Hirschfeldt, Miller and Podzorov proposed a seemingly simple notion of order-computable sets from the computable-model-theoretic point of view. However, their results reveal that there are no easy characterizations of order-computable sets from the perspective of pure computability theory. Hirschfeldt, Miller and Podzorov also analyzed the order-computability problem and left the conjecture on

Received April 30, 2024.
2020 *Mathematics Subject Classification.* Primary 03D80, 68Q15, 68Q17.
Key words and phrases. computability theory, order-computable sets, Δ^0_2 sets.

© The Author(s), 2025. Published by Cambridge University Press on behalf of The Association for Symbolic Logic.
0022-4812/00/0000-0000
DOI:10.1017/jsl.2025.5

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

the complexity of order-computable sets open. In this paper, we affirmatively answer the conjecture on the complexity of order-computable sets in [13].

Fix the standard linear order $(\mathbb{N}, <)$ on natural numbers of order type ω.

DEFINITION 1 [13]. A set A is order-computable if there is a computable structure $(\mathbb{N}, \prec, R)$ in the language of linear orders together with a unary predicate such that $(\mathbb{N}, \prec, R) \cong (\mathbb{N}, <, A)$.

As proved in [13], an order-computable set A can be computed via a special copy $(\mathbb{N}, \prec, R)$ of $(\mathbb{N}, <, A)$ with R the following standard sets:

(1) $R = F_k := \{0, 1, \dots, k-1\}$ if A is a finite set with size $|A| = k$;
(2) $\overline{R} = F_k := \{0, 1, \dots, k-1\}$ if A is a cofinite set such that the size of the complement $\overline{A}$ of A is $|\overline{A}| = k$;
(3) $R = E := \{2m : m \in \mathbb{N}\}$ if A is an infinite coinfinite set.

In the above standard cases, say that $\prec$ *order-computes* A. Let f be the predecessor function of the linear order $(\mathbb{N}, \prec)$ isomorphic to $(\mathbb{N}, <)$; that is, $f(x)$ is the number of predecessors of x under $\prec$ for all x. Then f is a permutation on the set of natural numbers and it can be computed via a $\emptyset'$ oracle, i.e., $f \leq_T \emptyset'$. Furthermore, for any n,

$$n \in A \Leftrightarrow f^{-1}(n) \in R.$$

Then $A \leq_T \emptyset'$. This implies that order-computable sets are Δ^0_2.

Computable sets are order-computable, but there are order-computable sets that are not computable. In [13], the authors proved various results on order-computable sets from the perspective of high/low hierarchy and Ershov hierarchy in pure computability theory. For instance, they proved that any low c.e. set is order-computable and that there is a low d.c.e. set that is not order-computable; they also showed that the Turing degree $\mathbf{0}'$ contains both order-computable sets and non order-computable sets.

Using the tool of computable predecessor approximation functions, Hirschfeldt, Miller, and Podzorov pointed out that the complexity of the property of being order-computable for a Δ^0_2 set is Σ^0_4, leaving the following two conjectures open.

– **Conjecture I:** The index set $\{e \in \mathbb{N} : W_e \text{ is order-computable}\}$ of c.e. order-computable sets is Σ^0_4-complete, where $W_0, W_1, \dots, W_e, \dots$ is an effective listing of all c.e. sets.
– **Conjecture II:** The index set $\{e \in \mathbb{N} : A_e \text{ is order-computable}\}$ of order computable sets is Σ^0_4-complete, where A_e is a Δ^0_2 set with index e. That is, the eth partial computable binary function φ^2_e is total and it satisfies the condition $(\forall x)[\lim_s \varphi^2_e(x, s) \downarrow = 0 \text{ or } 1]$; in this case, $A_e(x) = \lim_s \varphi^2_e(x, s)$ for all x.

In Section 3, we affirmatively answer the Conjectures I and II on the complexity of order-computable sets above.

The class of Δ^0_2 sets plays an important role in pure computability theory. It is also interesting to consider the complexity of Δ^0_2 sets themselves. We continue to prove that the index set of Δ^0_2 sets is Π^0_3-complete in Section 4.

The remaining sections are organized as follows. Section 2 provides basic notions of computability theory as well as basic properties of order-computable sets. Section 3 answers the conjectures of Hirschfeldt, Miller, and Podzorov on the complexity of

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

c.e. order-computable sets and of general order-computable sets. Finally, Section 4 proves the result on the complexity of Δ^0_2 sets.

§2. Preliminary. For basic notions of computability theory, refer to books such as [7, 16, 18, 19].

A function $f : A \to \mathbb{N}$ with domain A is *partial computable* if there is a Turing program that computes the value $f(x)$ for any $x \in A$. Based on the effective coding of all Turing programs, partial computable functions can be effectively listed as $\varphi_0, \varphi_1, \ldots, \varphi_e, \ldots$, where φ_e is the function computed by the eth Turing program. Similarly, all partial computable binary functions are listed as $\varphi^2_0, \varphi^2_1, \ldots, \varphi^2_e, \ldots$. A set is *computably enumerable* if it is the domain of a partial computable function. All computably enumerable (often abbreviated as c.e.) sets can be effectively enumerated as $W_0, W_1, \ldots, W_e, \ldots$ with $W_e = dom(\varphi_e) = \{x \in \mathbb{N} : \varphi_e(x)\downarrow\}$. Computable functions are those partial computable functions φ_e with domain the set of all natural numbers, i.e., φ_e is total. Computable sets are those with computable characteristic functions.

We now briefly introduce arithmetical hierarchy on sets. For $n \geq 2$, let $\langle \cdot, \cdots, \cdot \rangle : \mathbb{N}^n \to \mathbb{N}$ be an effective coding of n-tuples of natural numbers into natural numbers. For a set A,

(1) A is Σ^0_1 if there is a computable set B such that $A = \{x : \exists y[\langle x, y\rangle \in B]\}$.
(2) A is Π^0_1 if there is a computable set B such that $A = \{x : \forall y[\langle x, y\rangle \in B]\}$.
(3) For $n \geq 2$, A is Σ^0_n if there is a Π^0_{n-1} set B such that $A = \{x : \exists y[\langle x, y\rangle \in B]\}$.
   - Σ^0_2 sets are of the form $\{x : \exists y_1 \forall y_2 \langle x, y_1, y_2\rangle \in B\}$ with B a computable set.
   - Σ^0_4 sets are of the form $\{x : \exists y_1 \forall y_2 \exists y_3 \forall y_4 \langle x, y_1, y_2, y_3, y_4\rangle \in B\}$ with B a computable set.
(4) For $n \geq 2$, A is Π^0_n if there is a Σ^0_{n-1} set B such that $A = \{x : \forall y[\langle x, y\rangle \in B]\}$.
   - Π^0_2 sets are of the form $\{x : \forall y_1 \exists y_2 \langle x, y_1, y_2\rangle \in B\}$ with B a computable set.
   - Π^0_3 sets are of the form $\{x : \forall y_1 \exists y_2 \forall y_3 \langle x, y_1, y_2, y_3\rangle \in B\}$ with B a computable set.

For two sets $A, B \subseteq \mathbb{N}$, A is *many-one reducible* (i.e., *m-reducible*) to B, if there is a computable function $f : \mathbb{N} \to \mathbb{N}$ such that for all $x \in \mathbb{N}$, $x \in A \Leftrightarrow f(x) \in B$.

DEFINITION 2. For a complexity class Γ (e.g., Π^0_3, Σ^0_4), a Γ set A is *m*-complete Γ (or simply Γ-complete) if any Γ set B is *m*-reducible to A.

Let $W_0, W_1, \ldots, W_e, \ldots$ be the effective listing of all c.e. sets. The index sets of subclasses of c.e. sets provide typical examples of arithmetic complete sets.

(1) The index set $\mathrm{Tot} = \{e : W_e = dom(\varphi_e) = \mathbb{N}\}$ of (total) computable functions is Π^0_2-complete.
(2) The index set $\mathrm{Cof} = \{e : W_e \text{ is cofinite}\}$ of cofinite c.e. sets is Σ^0_3-complete.
(3) The index set of computable sets $\{e : W_e \text{ is computable}\}$ is Σ^0_3-complete.

By definition, Δ^0_2 sets are those that are both Σ^0_2 and Π^0_2. By Post's theorem, a set A is Δ^0_2 if and only if $A \leq_T \emptyset'$; furthermore, by Shoenfield limit lemma, A is Δ^0_2 if and only if there is a computable binary function f such that the characteristic function

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

of A is $A(x) = \lim_s f(x,s)\downarrow$ for all x. Based on the index of partial computable binary functions, we have the following index for a Δ^0_2 set.

DEFINITION 3. A number e is an index of a Δ^0_2 set A if the eth partial computable binary function φ^2_e is total and the characteristic function of A is $A(x) = \lim_s \varphi^2_e(x,s)\downarrow$ for all x.

For a number e, it becomes an index of some Δ^0_2 set if and only if the following conditions on e hold:

(1) φ^2_e is a computable function, that is, for all x, s, there is a stage t such that the computation $\varphi^2_{e,t}(x,s)$ converges at stage t;
(2) for all x, the limit $\lim_s \varphi^2_e(x,s)$ converges to 0 or 1.

First, (1) is Π^0_2; furthermore, similar to the fact that the index set of computable functions $\mathrm{Tot} = \{e \in \mathbb{N} : (\forall x)[\varphi_e(x)\downarrow]\}$ is Π^0_2-complete, the condition (1) is Π^0_2-complete. More specifically, the index set $\mathrm{Tot}^2 = \{e \in \mathbb{N} : (\forall x, y)[\varphi^2_e(x,y)\downarrow]\}$ of computable binary functions is Π^0_2-complete. Second, the condition (2) is Π^0_4 because it can be described by the following Π^0_4 formula:

$$(\forall x)(\exists s_x)(\forall s \geq s_x)(\exists t \geq s)[\varphi^2_{e,t}(x,s)\downarrow = \varphi^2_{e,t}(x,s_x)\downarrow = 0 \text{ or } 1].$$

The condition (2) is indeed Π^0_4-complete. We omit the detail proof here.

PROPOSITION 1. *The index set* $\{e \in \mathbb{N} : (\forall x)[\lim_s \varphi^2_e(x,s)\downarrow = 0 \text{ or } 1]\}$ *is* Π^0_4-*complete.*

For e to be a Δ^0_2 index, both conditions (1) and (2) hold. Then under the condition (1) that φ^2_e is total, the condition (2) becomes Π^0_3 because $\varphi^2_e(x,s)$ is always defined for all x, s. From the analysis above, we obtain the upper bound on the complexity of the index set $\mathcal{I}$ of Δ^0_2 sets. We further prove that $\mathcal{I}$ is Π^0_3-complete in Section 4.

PROPOSITION 2. *The index set* $\mathcal{I} = \{e \in \mathbb{N} : e \text{ is an index of a } \Delta^0_2 \text{ set}\}$ *is* Π^0_3.

We next review basic properties of order-computable sets, for more details, refer to [13]. Order-computable sets are always Δ^0_2 and they are closely connected with predecessor functions of linear orders that order-compute them. Such linear orders are of order type ω.

For a computable linear order of order type ω, the predecessor function of it can be approximated via partial computable binary functions in a natural way.

DEFINITION 4 [13]. A partial computable binary function f is a computable predecessor approximation function if it satisfies the following properties:

(1) for all n, s, $f(n,s)\downarrow$ if and only if $n < s$;
(2) for all s, $f(\cdot, s)$ is a permutation on $\{0, 1, \ldots, s-1\}$;
(3) for all $i < s$, $f(i,s) \leq f(i, s+1) \leq f(i,s) + 1$;
(4) for all n, $\lim_s f(n,s)$ exists.

For an order-computable set A order-computed via the linear order $\prec$, that is, $(\mathbb{N}, <, A)$ is isomorphic to the computable structure $(\mathbb{N}, \prec, R)$ with R the standard sets defined in introduction above, let

$$f_A(n,s) := \begin{cases} |\{x < s : x \prec n\}|, & \text{if } n < s \\ \uparrow, & \text{otherwise} \end{cases}$$

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

For $n < s$, $f_A(n,s)$ is the number of predecessors of n under the restricted order $(\mathbb{N}, \prec) \upharpoonright_s$ on the finite set $\{0,1,\dots,s-1\}$, and $f_A(\cdot,\cdot)$ is a computable predecessor approximation function such that

$$A := \begin{cases} \{\lim_s f_A(m,s) : 0 \le m \le k-1\}, & \text{if } (\exists k)[|A| = k] \\ \{\lim_s f_A(m,s) : m \ge k\}, & \text{if } (\exists k)[|\overline{A}| = k] \\ \{\lim_s f_A(2m,s) : m \ge 0\}, & \text{otherwise} \end{cases}$$

Conversely, consider the eth partial computable binary function $\varphi_e^2(\cdot,\cdot)$, if it is a computable predecessor approximation function under Definition 4, then for each $s \ge 1$, $\varphi_e^2(\cdot,s)$ is a permutation on $\{0,1,\dots,s-1\}$, so it determines a finite linear order $\mathcal{L}_s = (\{0,1,\dots,s-1\}, \prec_s)$ such that

$$|\{x < s : x \prec_s n\}| = \varphi_e^2(n,s),$$

and $\mathcal{L} = \bigcup_s \mathcal{L}_s = (\mathbb{N}, \prec)$ is a computable linear order on $\mathbb{N}$ of order type ω such that the number of predecessors of n is just $\lim_s \varphi_e^2(n,s)$. Then the following set

$$O_e := \{\lim_s \varphi_e^2(2m,s) : m \in \mathbb{N}\}$$

is an infinite coinfinite order-computable set, which is order-computed via the constructed order $\prec$. From this analysis, we see that any infinite coinfinite order-computable sets are of the form O_e for some e with φ_e^2 a computable predecessor approximation function.

The class of order-computable sets forms a subclass of Δ_2^0 sets. To study the complexity of order-computable sets by using indices of Δ_2^0 sets, rather than using usual m-reducibility, it is more suitable to consider the notion of m-reducibility within a given set proposed by Calvert and Knight, see [3, Definitions 3.1 and 3.2], see also [4, Definition 3.6].

DEFINITION 5 [3, 4]. Let $A \subseteq B$. A set S is m-reducible to A within B if there is a computable function $f : \mathbb{N} \to B$ such that for all x, $x \in S \Leftrightarrow f(x) \in A$.

Similar to the usual m-reducibility, we have the following Γ-completeness within a given set.

DEFINITION 6 [3, 4]. Let $A \subseteq B$ and Γ a complexity class (e.g., Π_3^0, Σ_4^0). A set A is m-complete Γ within a set B (or simply Γ-complete within B) if

(1) A is Γ within B; that is, there is a Γ set C such that $A = C \cap B$;
(2) any Γ set S is m-reducible to A within B.

We now consider the complexity of the index set of order-computable sets within the index set $\mathcal{I}$ of Δ_2^0 sets.

PROPOSITION 3 [13]. *The index set* $\{e \in \mathcal{I} : A_e \text{ is order-computable}\}$ *of order computable sets is* Σ_4^0 *within* $\mathcal{I}$.

PROOF. Let $e \in \mathcal{I}$. For all x, $A_e(x) = \lim_s \varphi_e^2(x,s) \downarrow$. A_e is order-computable if and only if one of the following three conditions hold:

(1) A_e is finite;
(2) A_e is cofinite;
(3) there is an index i such that

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

(3.1) φ_i^2 is a computable predecessor approximation function, and
(3.2) for any n, $n \in A_e$ if and only if $n = \lim_s \varphi_i^2(2m, s)$ for some m.

First of all, φ_e^2 is a computable approximation for the Δ_2^0 set A_e, that is, φ_e^2 is a total function such that for all x, $\lim_s \varphi_e^2(x, s)$ converges to 0 or 1. This can be described by the following Π_3^0 formula:

$$(\forall x, y)(\exists t)[\varphi_{e,t}^2(x, y) \downarrow] \wedge (\forall z)(\exists s_z)(\forall s \geq s_z)[\varphi_e^2(z, s) = \varphi_e^2(z, s_z)].$$

For (1), A_e is finite if and only if there is a large number N such that for all $n > N$, $A_e(n) = \lim_s \varphi_e^2(n, s) = 0$. This can be described by the Σ_4^0 formula:

$$(\exists N)(\forall n > N)(\exists s_n)(\forall s \geq s_n)[\varphi_e^2(n, s) = \varphi_e^2(n, s_n) = 0].$$

Similarly, A_e is cofinite if and only if

$$(\exists N)(\forall n > N)(\exists s_n)(\forall s \geq s_n)[\varphi_e^2(n, s) = \varphi_e^2(n, s_n) = 1].$$

Therefore, both (1) and (2) are Σ_4^0 properties on e.

Now consider the condition (3): there exists an index i satisfying (3.1) and (3.2). First, (3.1) says that φ_i^2 is a computable predecessor approximation function, which can be described by the following Π_3^0 formula:

$$\begin{aligned}
&(\forall s)(\forall n < s)(\exists t)[\varphi_{i,t}^2(n, s) \downarrow] \wedge \\
&(\forall s)(\forall n \geq s)(\forall t)[\varphi_{i,t}^2(n, s) \uparrow] \wedge \\
&(\forall s)(\forall n, m < s)[\varphi_i^2(n, s) < s \wedge (n \neq m \rightarrow \varphi_i^2(n, s) \neq \varphi_i^2(m, s))] \wedge \\
&(\forall s)(\forall n < s)[\varphi_i^2(n, s) \leq \varphi_i^2(n, s+1) \leq \varphi_i^2(n, s) + 1] \wedge \\
&(\forall n)(\exists s_n > n)(\forall s \geq s_n)[\varphi_i^2(n, s) = \varphi_i^2(n, s_n)].
\end{aligned}$$

Second, (3.2) says that for all n, $A_e(n) = 1 \Leftrightarrow n = \lim_s \varphi_i^2(2m, s)$ for some m. This condition can be expressed as

$$\begin{aligned}
(\forall n)(\exists m)(\exists t > n + 2m)(\forall s \geq t)[\varphi_e^2(n, s) = \varphi_e^2(n, t) = 1 \rightarrow \varphi_i^2(2m, s) \\
= \varphi_i^2(2m, t) = n] \wedge \\
(\forall n)(\forall m)(\exists t > n + 2m)(\forall s \geq t)[\varphi_e^2(n, s) = \varphi_e^2(n, t) = 0 \rightarrow \varphi_i^2(2m, s) \\
= \varphi_i^2(2m, t) \neq n].
\end{aligned}$$

Therefore, the condition (3) is a Σ_4^0 property on e.

For $e \in \mathcal{I}$, A_e is order-computable if and only the Σ_4^0 properties (1)–(3) on e hold. This shows that the index set of order-computable sets is Σ_4^0 within $\mathcal{I}$. ⊣

Similar to the case of general order-computable sets, we have the same upper bound for the complexity of c.e. order-computable sets.

PROPOSITION 4 [13]. *The index set* $\{e \in \mathbb{N} : W_e$ *is order-computable*$\}$ *of c.e. order-computable sets is* Σ_4^0.

§3. Order-computable sets. Let $\langle \Phi_e : e \in \mathbb{N} \rangle$ be an effective listing of all oracle Turing functionals. Fix the Halting set K. Then $\Phi_0^K, \Phi_1^K, \ldots, \Phi_e^K, \ldots$ is an effective listing of all partial computable functions relative to K and $W_0^K, W_1^K, \ldots, W_e^K, \ldots$ is

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

an effective listing of all c.e. sets relative to K with $W_e^K = \{x \in \mathbb{N} : \Phi_e^K(x)\downarrow\}$, the domain of Φ_e^K. At a stage s, a number x goes into $W_e^K[s]$ if $\Phi_e^K(x)[s]$ is defined with use $\phi_e^K(x)[s]$; we also say that $x \in W_e^K[s]$ with use $\phi_e^K(x)[s]$. For any number x, it belongs to W_e^K if and only if there is a stage s_x such that at any stage $t \geq s_x$, $x \in W_e^K[t]$ with use the same as $\phi_e^K(x)[s_x]$. In this case, the convergent computation $\Phi_e^K(x)[s_x]\downarrow$ does not change after stage s_x, and thus, x stays in W_e^K forever. Let $\mathrm{Cof}^K = \{e \in \mathbb{N} : W_e^K \text{ is cofinite}\}$. Then Cof^K is Σ_3^0-complete relative to the c.e. complete set K, and thus, it is Σ_4^0-complete.

THEOREM 1. *The index set of c.e. order-computable sets is Σ_4^0-complete.*

PROOF. An infinite coinfinite set A is order-computable if and only if there is a computable predecessor approximation function f such that for all n,

$$n \in A \Leftrightarrow (\exists m)[n = \lim_s f(2m, s)].$$

Consider the Σ_4^0-complete set $\mathrm{Cof}^K = \{e \in \mathbb{N} : W_e^K \text{ is cofinite}\}$. To prove the theorem, we enumerate a uniform sequence $\langle C_e : e \in \mathbb{N}\rangle$ of noncomputable c.e. sets such that for all e,

$$e \in \mathrm{Cof}^K \Leftrightarrow C_e \text{ is order-computable.}$$

For $e \in \mathrm{Cof}^K$, we build C_e to be low so that it is order-computable, because low c.e. sets are order-computable (see [13, Theorem 2.6]). On the other hand, for $e \notin \mathrm{Cof}^K$, to ensure the non order-computability of C_e, we construct C_e to be not order-computed by φ_i^2 for any i; that is, $C_e \neq O_i = \{\lim_s \varphi_i^2(2m, s) : m \in \mathbb{N}\}$ if φ_i^2 does become a computable predecessor approximation function. ⊣

3.1. Requirements and strategies. We enumerate a uniform sequence of c.e. sets $\langle C_e : e \in \mathbb{N}\rangle$ such that the following requirements are satisfied.

(1) $\mathcal{P}_{\langle e,i\rangle}$: $C_e \neq \varphi_i$.

(2) $\mathcal{R}_{\langle e,i,i+j\rangle}$: If $[i, i+j+1] \subseteq W_e^K$ and $(\exists^\infty s)[\Phi_j^{C_e}(j)[s]\downarrow]$, then $\Phi_j^{C_e}(j)\downarrow$.
If $[i, i+j+1] \nsubseteq W_e^K$ and φ_i^2 is a computable predecessor approximation function, then $C_e \neq O_i = \{\lim_s \varphi_i^2(2m, s) : m \in \mathbb{N}\}$.

Here, $\langle \varphi_i : i \in \mathbb{N}\rangle$, $\langle \varphi_i^2 : i \in \mathbb{N}\rangle$ and $\langle \Phi_j : j \in \mathbb{N}\rangle$ are effective listing of partial computable functions, partial computable binary functions and oracle Turing functionals, respectively.

For each e, all $\mathcal{P}_{\langle e,i\rangle}$-requirements with $i \in \mathbb{N}$ together ensure the noncomputability of C_e. For $e \in \mathrm{Cof}^K$, W_e^K is cofinite; that is, there is a number i such that $[i, \infty) \subseteq W_e^K$. In this case, for all j, $[i, i+j+1] \subseteq W_e^K$, and the requirement $\mathcal{R}_{\langle e,i,j\rangle}$ ensures that the computation $\Phi_j^{C_e}(j)$ converges if and only if there are infinitely many stages s such that $\Phi_j^{C_e}(j)$ converges at stage s. This implies that $C_e' = \{j \in \mathbb{N} : \Phi_j^{C_e}(j)\downarrow\}$ is Δ_2^0 and thus $C_e' \leq_T \emptyset'$, i.e., C_e is low. As low c.e. sets are order-computable, C_e is order-computable. On the other hand, for $e \notin \mathrm{Cof}^K$, W_e^K is not cofinite. Then for all $i \in \mathbb{N}$, there exists a number j_i such that $[i, i+j_i+1] \nsubseteq W_e^K$, and the requirement $\mathcal{R}_{\langle e,i,j_i\rangle}$ ensures that C_e is not order-computed by φ_i^2. So C_e is not order-computable.

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

The construction of c.e. sets $\langle C_e : e \in \mathbb{N}\rangle$ proceeds on a priority tree T whose nodes are assigned $\mathcal{P}$- and $\mathcal{R}$-requirements. We view each node α as a strategy for satisfying the assigned requirement whose possible outcomes are immediate successors of α on T. A $\mathcal{P}$-strategy has two possible outcomes d, f with priority $d <_L f$ on the priority tree T. While an $\mathcal{R}$-strategy has three possible outcomes ∞, d, f with priority $\infty <_L d <_L f$ on T. We assign $\mathcal{P}$-requirements to nodes of length even and assign $\mathcal{R}$-requirements to nodes of length odd. So the priority tree T is simply a subtree of the full tree $S = \{\infty, d, f\}^{<\omega}$ of finite strings on $\{\infty, d, f\}$, where S has the usual lexicographic order such that $\alpha^\frown\infty <_L \alpha^\frown d <_L \alpha^\frown f$ for any $\alpha \in S$.

DEFINITION 7. The priority tree T is defined as follows.

(1) Let the empty node $\lambda \in T$.
(2) Let $\alpha \in T$ with length $|\alpha| \geq 0$.
   - If $|\alpha|$ is even, add $\alpha^\frown d$ and $\alpha^\frown f$ into T.
   - If $|\alpha|$ is odd, add $\alpha^\frown\infty$, $\alpha^\frown d$ and $\alpha^\frown f$ into T.

At each stage s of the construction, we will define a current approximation $\delta_s \in T$ of the true path $\mathrm{TP} = \liminf_s \delta_s$ of the construction. TP will be an infinite path on the priority tree T. For any node $\alpha \in T$, when $\alpha \subseteq \delta_s$, say that α is *visited* at stage s, and call s an α-*stage*.

For ease of description, we often write the $\mathcal{P}_{\langle e,i\rangle}$-requirement assigned to a node $\alpha \in T$ as $\mathcal{P}_{\langle e(\alpha),i(\alpha)\rangle}$ (or simply $\mathcal{P}_\alpha$) with $e(\alpha) = e$ and $i(\alpha) = i$. Similarly, we write the $\mathcal{R}_{\langle e,i,j\rangle}$-requirement assigned to a node $\beta \in T$ as $\mathcal{R}_{\langle e(\beta),i(\beta),j(\beta)\rangle}$ (or simply $\mathcal{R}_\beta$) with $e(\beta) = e$, $i(\beta) = i$ and $j(\beta) = j$. In the following, we first give a basic $\mathcal{P}$- and $\mathcal{R}$-strategy for satisfying a single $\mathcal{P}$- and $\mathcal{R}$-requirement, respectively, and then define the assignment of the requirements to the priority tree T.

A basic $\mathcal{P}_{\langle e,i\rangle}$-strategy. Let α be a node of length even on the priority tree T assigned the $\mathcal{P}_{\langle e,i\rangle}$-requirement. A basic α-strategy works to diagonalize against $C_e = \varphi_i$ at α-stages.

(1) At the first α-stage s, choose a new witness $w_{\alpha,s}$ and a set of fresh *trigger* elements $\{x^k_{\alpha,s} : 1 \leq k \leq q_\alpha = 2^{3^{|\alpha|+1}}\}$ for higher priority $\mathcal{R}$-strategies β with $C_{e(\beta)} = C_{e(\alpha)}$ on the priority tree T to enumerate into $C_{e(\beta)}$ later such that
$$N_{\alpha,s} < x^1_{\alpha,s} < x^2_{\alpha,s} < \ldots < x^{q_\alpha}_{\alpha,s} < w_{\alpha,s},$$
where $N_{\alpha,s}$ is a new number larger than all used numbers before; particularly, $N_{\alpha,s}$ is bigger than all restraints $r(\beta, s)$ appointed on $C_{e(\beta)}$ by $\mathcal{R}$-strategies $\beta < \alpha$ (i.e., $\beta <_L \alpha$ or $\beta \subset \alpha$).
   The witness $w_{\alpha,s}$ and the triggers $x^k_{\alpha,s} (1 \leq k \leq q_\alpha)$ keep unchanged at later stages unless the node α is initialized by higher priority strategies.
(2) Wait for an α-stage $t > s$ such that $\varphi_{i,t}(w_{\alpha,s}) \downarrow = 0$.
(3) Put $w_{\alpha,s}$ into $C_{e,t}$.

The possible outcomes of a basic α-strategy are the following:

f : wait at Step (2) forever; in this case, either φ_i is not total or $\varphi_i(w_{\alpha,s}) \downarrow = 1 \neq C_e(w_{\alpha,s}) = 0$;
d : arrive at Step (3); in this case, $\varphi_i(w_{\alpha,s}) \downarrow = 0 \neq C_e(w_{\alpha,s}) = 1$.

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

In both cases, the strategy ensures that $C_e \neq \varphi_i$. The priority of the two outcomes on the priority tree is $d <_L f$.

A basic $\mathcal{R}_{\langle e,i,j\rangle}$-strategy. Let α be a node of length odd on the priority tree T assigned the $\mathcal{R}_{\langle e,i,j\rangle}$-requirement. First, define the following notion of expansionary stages to approximate the condition $[i, i+j+1] \subseteq W_e^K$. Since the condition $[i, i+j+1] \subseteq W_e^K$ is Σ_2^0, as in usual infinite injury constructions, we ensure that the Σ_2^0 condition $[i, i+j+1] \subseteq W_e^K$ holds if and only if there are finitely many expansionary stages during the construction.

DEFINITION 8. Let s be an α-stage. If there was a last α-stage s^- such that $[i, i+j+1] \subseteq W_e^K[s^-]$ and for all $x \in [i, i+j+1]$, $x \in W_e^K[s]$ with use the same as $\phi_e^K(x)[s^-]$, then s is called a non α-expansionary stage; otherwise, s is called an α-expansionary stage.

Supposed that α is visited infinitely often during the construction. The Σ_2^0 condition $[i, i+j+1] \subseteq W_e^K$ is true if and only if there is an α-stage s such that every α-stage $t \geq s$ is a non α-expansionary stage. An α-strategy works to satisfy its requirement $\mathcal{R}_{\langle e,i,j\rangle}$. At a non α-expansionary stage s, it prevents numbers from enumerating into C_e to preserve convergent computations of the form $\Phi_j^{C_e}(j)[s]\downarrow$. While at an α-expansionary stage s, it devotes to diagonalize against φ_i^2 to be a computable predecessor approximation function for C_e by enumerating numbers into C_e.

Second, to measure the approximation of the order-computable set O_i computed by φ_i^2, define the following length function $l(i,s)$ of O_i.

(1) If there is a number $x \in [1, s]$ such that the following conditions hold:
- $\varphi_{i,s}^2(n,x)\downarrow < x$ for all $n < x$, and $\varphi_{i,s}^2(m,x)\uparrow$ for all $x \leq m \leq s$;
- $\varphi_{i,s}^2(\cdot, x)$ is a permutation on $\{0, 1, \ldots, x-1\}$;
- $\varphi_{i,s}^2(n,t) \leq \varphi_{i,s}^2(n,t+1) \leq \varphi_{i,s}^2(n,t)+1$ for all $n < t < x$;

let $l(i,s)$ be the largest such a number x, and define

$$O_{i,s} = \{\varphi_{i,s}^2(2m, l(i,s)) : 2m < l(i,s)\}.$$

(2) Otherwise, such a number x does not exist, let $l(i,s) = 0$ and $O_{i,s} = \emptyset$.

If φ_i^2 does become a computable predecessor approximation function, then we have $\lim_s l(i,s) = \infty$, and the corresponding order-computable set is

$$O_i = \lim_s O_{i,s} = \{\lim_s \varphi_i^2(2m, s) : m \in \mathbb{N}\}.$$

In order to diagonalize against φ_i^2 to be a computable predecessor approximation function for C_e, an α-strategy aims to make sure that either $\lim_s l(i,s) < \infty$, or $\lim_s \varphi_i^2(y,s) = \infty$ for some even number y, or φ_i^2 really becomes a computable predecessor approximation function with $\lim_s l(i,s) = \infty$ but $C_e(x) \neq O_i(x)$ for some x; that is, there is a large stage s_x such that for all $t \geq s_x$, $C_{e,t}(x) \neq O_{i,t}(x)$. This analysis motivates us to formally define the following approximation of the length of agreement between C_e and O_i. The idea behind this definition was already used in [13, Theorem 3.11] to build a Turing degree which contains no order-computable sets.

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

DEFINITION 9. Say that φ_i^2 appears to be a computable predecessor approximation function for C_e at an α-stage s if $l(i,s) > 0$, $l(i,s) > l(i,t)$ for all α-stages $t < s$, and $C_{e,s} = \{\varphi_{i,s}^2(2m, l(i,s)) : 2m < l(i,s)\} = O_{i,s}$.

A basic α-strategy acts to satisfy its requirement $\mathcal{R}_{\langle e(\alpha), i(\alpha), j(\alpha)\rangle}$ with $e(\alpha) = e$, $i(\alpha) = i$ and $j(\alpha) = j$ at α-stages as follows. There are two cases:

Case 1. At a non α-expansionary stage s, an α-strategy proceeds to preserve the computation $\Phi_j^{C_e}(j)[s]$. Let $\phi_j^{C_e}(j)[s]$ denote the use of the computation $\Phi_j^{C_e}(j)[s]$ if it converges.

(1) If $\Phi_j^{C_e}(j)[s]$ converges, appoint a restraint $r(\alpha, s) = \phi_j^{C_e}(j)[s]$ on C_e to preserve the computation $\Phi_j^{C_e}(j)[s]$.
(2) If $\Phi_j^{C_e}(j)[s]$ diverges, set $r(\alpha, s) = 0$.

Any lower priority β-strategy on T can only enumerate numbers $> r(\alpha, s)$ into $C_{e(\beta)}$ later.

Case 2. At α-expansionary stages, a basic α-strategy acts to diagonalize against φ_i^2 to be a computable predecessor approximation function for C_e.

(1) At the first α-expansionary stage s_0, choose a large new witness w_{α,s_0} and a set of fresh *trigger* elements $\{x_{\alpha,s_0}^k : 1 \le k \le q_\alpha = 2^{3^{|\alpha|+1}}\}$ for higher priority $\mathcal{R}$-strategies β with $e(\beta) = e(\alpha)$ and $\beta \le \alpha$ (i.e., $\beta <_L \alpha$ or $\beta \subseteq \alpha$) to enumerate into $C_{e(\beta)}$ later such that

$$N_{\alpha,s_0} < x_{\alpha,s_0}^1 < x_{\alpha,s_0}^2 < \ldots < x_{\alpha,s_0}^{q_\alpha} < w_{\alpha,s_0},$$

where N_{α,s_0} is a new number larger than all used numbers before; particularly, N_{α,s_0} is bigger than all restraints $r(\beta, s_0)$ appointed on $C_{e(\beta)}$ by $\mathcal{R}$-strategies β with $\beta < \alpha$.
• Enumerate w_{α,s_0} into $C_{e(\alpha),s_0}$.
The witness w_{α,s_0} and the triggers $x_{\alpha,s_0}^k (1 \le k \le q_\alpha)$ keep unchanged at later stages unless the node α is initialized by higher priority strategies.
(2) Wait for an α-expansionary stage $t_0 > s_0$ such that the length approximation of the order-computable set $l(i(\alpha), t_0) > w_{\alpha,s_0}$, and $\varphi_{i(\alpha)}^2$ appears to be a computable predecessor approximation function for $C_{e(\alpha)}$ at stage t_0.
(3) Let y_{α,t_0} be the unique even number such that $\varphi_{i(\alpha)}^2(y_{\alpha,t_0}, l(i(\alpha), t_0)) = w_{\alpha,s_0} \in C_{e(\alpha),s_0}$.
• Pick the largest trigger element $x_{\alpha,s_0}^k < w_{\alpha,s_0}$ that has not been enumerated into $C_{e(\beta)}$ by β-strategies with $\beta < \alpha$.
• Enumerate x_{α,s_0}^k into $C_{e(\alpha),t_0}$.
• Go to Step $(4.n)$ with $n = 1$.
The even number y_{α,t_0} remains the same at later stages as long as α is not initialized.
$(4.n)$ Wait for an α-expansionary stage $t_n > t_{n-1}$ such that $\varphi_{i(\alpha)}^2$ appears to be a computable predecessor approximation function for $C_{e(\alpha)}$ at stage t_n.
$(5.n)$ Let $u_{\alpha,t_0} = w_{\alpha,s_0}$ and $u_{\alpha,t_n} = \varphi_{i(\alpha)}^2(y_{\alpha,t_0}, l(i(\alpha), t_n))$. Then we have

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

$$w_{\alpha,s_0} \leq u_{\alpha,t_{n-1}} = \varphi^2_{i(\alpha)}(y_{\alpha,t_0}, l(i(\alpha), t_{n-1})) < \varphi^2_{i(\alpha)}(y_{\alpha,t_0}, l(i(\alpha), t_n)) = u_{\alpha,t_n} \in O_{i(\alpha),t_n} = C_{e(\alpha),t_n}$$

because the enumeration of the trigger element $x^k_{\alpha,s_0} < w_{\alpha,s_0}$ in Step (3) for $n = 1$ or $x^k_{\beta,t} \in (w_{\alpha,s_0}, u_{\alpha,t_{n-1}})$ in Step (5. $(n-1)$) for $n \geq 2$ forces the number of predecessors of y_{α,t_0} computed by $\varphi^2_{i(\alpha)}$ to move up.

As $u_{\alpha,t_n} \in C_{e(\alpha),t_n}$ and $u_{\alpha,t_n} > w_{\alpha,s_0}$, there is a unique node $\beta > \alpha$ on the priority tree T such that

$$u_{\alpha,t_n} = w_{\beta,t} \text{ or } u_{\alpha,t_n} = x^k_{\beta,t} \text{ for some } k,$$

where $w_{\beta,t}$ and $x^k_{\beta,t} (1 \leq k \leq q_\beta = 2^{3^{|\beta|+1}})$ were first appointed on β at some β-stage $t \in (t_0, t_n)$.

- Pick the largest trigger number $x^k_{\beta,t} < u_{\alpha,t_n} \leq w_{\beta,t}$ that has not been enumerated into $C_{e(\beta')}$ for any $\beta' \leq \beta$.
- Enumerate $x^k_{\beta,t}$ into $C_{e(\alpha),t_n}$.
- Go to Step $(4.(n+1))$.

For each node $\beta \in T$, since the number of nodes $\beta' \in T$ with $\beta' <_L \beta$ or $\beta' \subseteq \beta$ is strictly less than $3^{|\beta|+1}$, we appoint enough (i.e., $2^{3^{|\beta|+1}}$ many) trigger elements $x^k_{\beta,t}$ on node β for higher priority β'-strategies working for $\mathcal{R}$-requirements to enumerate into $C_{e(\beta')}$ during the construction. That is, the trigger elements in Step (3) or Step (5.n) always exist if needed (see Lemma 1 below).

The possible outcomes of a basic α-strategy is listed as follows:

f: finitely many α-expansionary stages;
d: wait at Step (2) or Step $(4.n)$ for some $n \geq 1$ forever at α-expansionary stages;
∞: go to Step $(4.(n+1))$ from Step $(5.n)$ infinitely often at α-expansionary stages.

The priority of the outcomes on the priority tree T is $\infty <_L d <_L f$.

If there are finitely many α-expansionary stages, α has the finite outcome f, and the computation $\Phi^{C_{e(\alpha)}}_{j(\alpha)}(j(\alpha))$ will be preserved after certain stage if it converges at infinitely many α-stages. If there are infinitely many α-expansionary stages, α has two possible outcomes $\infty <_L d$.

(i) If α has the outcome d, then either $\lim_s l(i(\alpha), s) < \infty$ or $C_{e(\alpha)} \neq O_{i(\alpha)}$ in which case α only enumerates finitely many triggers into $C_{e(\alpha)}$.
(ii) If α has the outcome ∞, then $\lim_s \varphi^2_{i(\alpha)}(y_{\alpha,t_0}, s) = \lim_n u_{\alpha,t_n} = \infty$ in which case α enumerates infinitely many triggers into $C_{e(\alpha)}$.

In both cases, $\varphi^2_{i(\alpha)}$ cannot be a computable predecessor approximation function for $C_{e(\alpha)}$. In other words, $C_{e(\alpha)}$ is not order-computed via $\varphi^2_{i(\alpha)}$.

This ends the description of basic strategies.

Fix a bijection $\langle \cdot, \cdot \rangle : \mathbb{N}^2 \to \mathbb{N}$ such that $\langle e, i \rangle < \langle e, i' \rangle$ for all e, i, i' with $i < i'$. For $e, i, j \in \mathbb{N}$, let $\langle e, i, j \rangle = \langle \langle e, i \rangle, j \rangle$. Then we can fix a linear order $\prec$ on all $\mathcal{P}_{\langle e,i \rangle}$- and $\mathcal{R}_{\langle e,i,j \rangle}$-requirements $(e, i, j \in \mathbb{N})$ of order type ω as follows.

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

(1) For all e, i, e', i', let $\mathcal{P}_{\langle e,i\rangle} \prec \mathcal{P}_{\langle e',i'\rangle}$ if and only if $\langle e, i\rangle < \langle e', i'\rangle$, and let the priority of all $\mathcal{P}$-requirements be listed as

$$\mathcal{P}_{\langle e_0,i_0\rangle} \prec \mathcal{P}_{\langle e_1,i_1\rangle} \prec \ldots \prec \mathcal{P}_{\langle e_n,i_n\rangle} \prec \ldots.$$

Particularly, for any number e, we have

$$\mathcal{P}_{\langle e,0\rangle} \prec \mathcal{P}_{\langle e,1\rangle} \prec \ldots \prec \mathcal{P}_{\langle e,i\rangle} \prec \ldots.$$

(2) For all e, i, j, e', i', j', let $\mathcal{R}_{\langle e,i,j\rangle} \prec \mathcal{R}_{\langle e',i',j'\rangle}$ if and only if $\langle e, i, j\rangle < \langle e', i', j'\rangle$, and let the priority of all $\mathcal{R}$-requirements be listed as

$$\mathcal{R}_{\langle e'_0,i'_0,j'_0\rangle} \prec \mathcal{R}_{\langle e'_1,i'_1,j'_1\rangle} \prec \ldots \prec \mathcal{R}_{\langle e'_n,i'_n,j'_n\rangle} \prec \ldots.$$

Particularly, for fixed numbers e, i, we have

$$\mathcal{R}_{\langle e,i,0\rangle} \prec \mathcal{R}_{\langle e,i,1\rangle} \prec \ldots \prec \mathcal{R}_{\langle e,i,j\rangle} \prec \ldots.$$

(3) Define the priority of all $\mathcal{P}$- and $\mathcal{R}$- requirements as

$$\mathcal{P}_{\langle e_0,i_0\rangle} \prec \mathcal{R}_{\langle e'_0,i'_0,j'_0\rangle} \prec \mathcal{P}_{\langle e_1,i_1\rangle} \prec \mathcal{R}_{\langle e'_1,i'_1,j'_1\rangle} \prec \ldots \prec \mathcal{P}_{\langle e_n,i_n\rangle} \prec \mathcal{R}_{\langle e'_n,i'_n,j'_n\rangle} \prec \ldots.$$

The tree of strategies. The priority tree T of the construction is a subtree of $S = \{\infty, d, f\}^{<\omega}$ such that any node $\alpha \in T$ of length even has two immediate extensions $\alpha^\frown d$ and $\alpha^\frown f$ on T and any node $\alpha \in T$ of length odd has three immediate extensions $\alpha^\frown\infty$, $\alpha^\frown d$ and $\alpha^\frown f$ on T. Say that a node $\alpha \in T$ is a $\mathcal{P}_{\langle e,i\rangle}$- or an $\mathcal{R}_{\langle e,i,j\rangle}$-strategy if it is assigned the corresponding requirement. As before, we write the $\mathcal{P}_{\langle e,i\rangle}$-requirement assigned to a node α of T with length even as $\mathcal{P}_{\langle e(\alpha),i(\alpha)\rangle}$ (or simply $\mathcal{P}_\alpha$). Similarly, we write the $\mathcal{R}_{\langle e,i,j\rangle}$-requirement assigned to a node β of T with length odd as $\mathcal{R}_{\langle e(\beta),i(\beta),j(\beta)\rangle}$ (or simply $\mathcal{R}_\beta$).

According to the priority of $\mathcal{P}$-, $\mathcal{R}$-requirements above, assign the requirements to nodes of the priority tree T by induction on their length as follows.

(1) For the empty node $\lambda \in T$, assign the highest priority $\mathcal{P}$-requirement $\mathcal{P}_{\langle e_0,i_0\rangle}$ to node λ.

(2) For nodes $d, f \in T$, assign the highest priority $\mathcal{R}$-requirement $\mathcal{R}_{\langle e'_0,i'_0,j'_0\rangle}$ to d, f.

(3) Assume that $\alpha = \alpha^-{}^\frown o \in T$ with length $|\alpha| \geq 1$. There are two cases depending on the parity of $|\alpha|$.

- If $|\alpha|$ is odd, then $\alpha^\frown\infty$, $\alpha^\frown d$ and $\alpha^\frown f \in T$. Suppose that the immediate predecessor α^- of α is assigned the $\mathcal{P}_{\langle e_n,i_n\rangle}$-requirement with $n \geq 0$.
  - For $o \in \{\infty, d, f\}$, assign $\mathcal{P}_{\langle e_{n+1},i_{n+1}\rangle}$ to node $\alpha^\frown o$.
- If $|\alpha|$ is even, then $\alpha^\frown d$ and $\alpha^\frown f \in T$. Suppose that the immediate predecessor α^- of α is assigned the $\mathcal{R}_{\langle e'_n,i'_n,j'_n\rangle}$-requirement with $n \geq 0$.
  - For $o \in \{d, f\}$, find the least $m > n$ such that $\langle e'_m, i'_m\rangle \neq \langle e(\beta), i(\beta)\rangle$ for all nodes β of length odd assigned the $\mathcal{R}_{\langle e(\beta),i(\beta),j(\beta)\rangle}$-requirement with $\beta^\frown d \subseteq \alpha$ or $\beta^\frown\infty \subseteq \alpha$, and assign $\mathcal{R}_{\langle e'_m,i'_m,j'_m\rangle}$ to node $\alpha^\frown o$.

Note that a node $\beta^\frown o \in T$ with $|\beta|$odd and $o \in \{d, \infty\}$represents that the β-strategy has an infinite outcome o. In this case, $[i(\beta), i(\beta) + j(\beta) + 1] \nsubseteq W^K_{e(\beta)}$ and the β-strategy works to diagonalize against $\varphi^2_{i(\beta)}$ to be a computable predecessor approximation function for $C_{e(\beta)}$. So we do not need to assign $\mathcal{R}_{\langle e(\beta),i(\beta),\cdot\rangle}$-requirements to nodes of T below $\beta^\frown o$.

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

We now describe possible conflictions between multiple $\mathcal{R}$-strategies on the priority tree T. Let α be an $\mathcal{R}_{\langle e,i,j\rangle}$-strategy on T. Suppose that $[i, i+j+1] \not\subseteq W_e^K$. For all $j' > j$, as $[i, i+j+1] \subseteq [i, i+j'+1]$, we have $[i, i+j'+1] \not\subseteq W_e^K$. So we do not need to assign $\mathcal{R}_{\langle e,i,j'\rangle}$ requirements with $j' > j$ to nodes below the infinite outcomes of α (i.e., below $\alpha^\frown d$ or $\alpha^\frown\infty$) on the priority tree. However, for $i' \neq i$, $\mathcal{R}_{\langle e,i',\cdot\rangle}$-requirements are still assigned to nodes below the infinite outcomes of α. Let $\alpha' \supset \alpha$ be an $\mathcal{R}_{\langle e,i',j'\rangle}$-strategy on T.

(i) If $\alpha^\frown d \subset \alpha'$, then there are no conflictions because α only enumerates finitely many triggers of nodes with lower priority into C_e.

(ii) If $\alpha^\frown\infty \subset \alpha'$, then α acts infinitely often to enumerate triggers of nodes $\beta \in T$ with $\beta > \alpha$ into C_e to force $\lim_s \varphi_i^2(y,s) = \infty$ for some even number y; this may injure a convergent computation $\Phi_{j'}^{C_e}(j')[s]\downarrow$, which α' needs to preserve, infinitely often. Since the triggers enumerated by α during the construction tend to infinity, to deal with this problem, we only preserve believable computations $\Phi_{j'}^{C_e}(j')[s]\downarrow$ where α will not enumerate triggers $< \phi_{j'}^{C_e}(j')[s]$, the use of the computation, after stage s.

DEFINITION 10. Let $\alpha' \in T$ be an $\mathcal{R}_{\langle e,i',j'\rangle}$-strategy. A convergent computation $\Phi_{j'}^{C_e}(j')[s]\downarrow$ is believable at a non α'-expansionary stage s if for any $\mathcal{R}$-strategy $\alpha \in T$ with $e(\alpha) = e$ and $\alpha^\frown\infty \subset \alpha'$, the α-strategy acts as in Step $(5.n)$ for some $n \geq 1$ to enumerate a trigger $x_{\beta,t}^k$ of some node $\beta > \alpha$ into C_e at stage s, then the use of the convergent computation $\phi_{j'}^{C_e}(j')[s]$ is strictly less than $x_{\beta,t}^1$, where $x_{\beta,t}^1 < \ldots < x_{\beta,t}^{q_\beta}$ with $q_\beta = 2^{3^{|\beta|+1}}$ are all triggers of the node β first defined at some β-stage $t < s$.

3.2. Construction and verification. We are ready to provide a formal construction of the c.e. sets $C_e (e \in \mathbb{N})$ by stages according to the tree of strategies.

Construction.

Stage 0. Let $\delta_0 = \lambda$, the empty node on T. Initialize all nodes on T. For all e, let $C_{e,0} = \emptyset$. For all nodes $\alpha \in T$ with length $|\alpha|$ odd, set the $C_{e(\alpha)}$-restraint $r(\alpha, 0) = 0$.

Stage $s \geq 1$. Define the current true path $\delta_s \in T$ with length $|\delta_s| \leq s$ at substages m with $0 \leq m \leq s-1$, starting at substage 0. Let $\alpha_0 = \lambda$, the empty node on T, and assume that we have defined $\alpha_m = \delta_s(0)\ldots\delta_s(m-1)$ by the end of substage $m-1$ for $1 \leq m \leq s$.

Substage $m (0 \leq m \leq s-1)$. Define the current true outcome $\delta_s(m)$ of α_m and enumerate numbers into $C_{e(\alpha_m),s}$ according to the basic α_m-strategy with additional initializations to strategies with lower priority on the priority tree T.

– If a node $\alpha \in T$ is initialized at stage s, then the witness $w_{\alpha,s}$ and triggers $x_{\alpha,s}^k (1 \leq k \leq q_\alpha = 2^{3^{|\alpha|+1}})$ are undefined.

– If $m = s-1$, let $\delta_s = \alpha_m{}^\frown\delta_s(m) = \alpha_{s-1}{}^\frown\delta_s(s-1) = \delta_s(0)\ldots\delta_s(s-1)$. Initialize all nodes $\alpha \geq \delta_s$, also initialize all nodes of length $\geq s+1$. End current stage s and go to next stage.

Substage m proceeds as follows. There are two cases depending on the parity of m.

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

Case I. If m is even, then α_m is a $\mathcal{P}$-strategy. Check whether there was a last α_m-stage s^- such that α_m has not been initialized since then.

(1) If such a last α_m-stage s^- did not exist, then s is the first α_m-stage after last initialization. Act as in the basic α_m-strategy.

- Choose a large new witness $w_{\alpha_m,s}$ and a set of fresh *trigger* elements $\{x^k_{\alpha_m,s} : 1 \leq k \leq q_{\alpha_m} = 2^{3^{|\alpha_m|+1}}\}$ for β-strategies with $|\beta|$ odd and $\beta \leq \alpha_m$ (i.e., $\beta <_L \alpha_m$ or $\beta \subseteq \alpha_m$) on the priority tree T to enumerate into $C_{e(\beta)}$ later such that

$$N_{\alpha_m,s} < x^1_{\alpha_m,s} < x^2_{\alpha_m,s} < \ldots < x^{q_{\alpha_m}}_{\alpha_m,s} < w_{\alpha_m,s},$$

  where $N_{\alpha_m,s}$ is a new number larger than all used numbers before; particularly, $N_{\alpha_m,s}$ is bigger than all restraints $r(\beta, s)$ appointed on $C_{e(\beta)}$ by higher priority β-strategies.
- Go to Step (2); that is, wait for $\varphi_{i(\alpha_m)}(w_{\alpha_m,s}) \downarrow = 0$.
- Let $\delta_s(m) = f$. Define $\delta_s = \alpha_m{}^\frown\delta_s(m) = \alpha_m{}^\frown f$. Initialize all nodes $\alpha \geq \alpha_m{}^\frown f$, also initialize all nodes of length $\geq s+1$.
- End Stage s and go to next stage.

The witness $w_{\alpha_m,s}$ and the triggers $x^k_{\alpha_m,s}(1 \leq k \leq q_{\alpha_m})$ keep unchanged at later stages unless the node α_m is initialized by higher priority strategies.

(2) If such a last α_m-stage s^- did exist, then there was a largest α_m-stage $s_0 \leq s^- < s$ such that the witness w_{α_m,s_0} and trigger elements $x^k_{\alpha_m,s_0}$ with $1 \leq k \leq q_{\alpha_m} = 2^{3^{|\alpha_m|+1}}$ were defined at stage s_0 and α_m has not been initialized since then. Define the current outcome $\delta_s(m)$ of the α_m-strategy started at stage s_0 according to the current state of the strategy.

- If the α_m-strategy waits at Step (2), let $\delta_s(m) = f$.
  - Initialize all nodes $\alpha >_L \alpha_m{}^\frown f$. Go to substage $m+1$ of current stage s if $m+1 < s$.
- If the α_m-strategy currently arrives at Step (2), act as in Step (3).
  - Enumerate w_{α_m,s_0} into $C_{e(\alpha_m),s}$.
  - Let $\delta_s(m) = d$. Define $\delta_s = \alpha_m{}^\frown\delta_s(m) = \alpha_m{}^\frown d$. Initialize all nodes $\alpha \geq \alpha_m{}^\frown d$ and all nodes of length $\geq s+1$.
  - End Stage s and go to next stage.
- Otherwise, the α_m-strategy was already arrived at Step (2) at last α_m-stage s^-, let $\delta_s(m) = d$.
  - Initialize all nodes $\alpha >_L \alpha_m{}^\frown d$. Go to substage $m+1$ of current stage s if $m+1 < s$.

Case II. If m is odd, then α_m is an $\mathcal{R}$-strategy. Act as follows.

Case 1. If s is a non α_m-expansionary stage, let $\delta_s(m) = f$. Act as in the basic α_m-strategy.

(1) If the computation $\Phi^{C_{e(\alpha_m)}}_{j(\alpha_m)}(j(\alpha_m))[s]$ newly converges and it is a believable computation at stage s, let $\phi^{C_{e(\alpha_m)}}_{j(\alpha_m)}(j(\alpha_m))[s]$ be the use of the computation.

- Appoint a new $C_{e(\alpha_m)}$-restraint $r(\alpha_m, s) = \phi^{C_{e(\alpha_m)}}_{j(\alpha_m)}(j(\alpha_m))[s]$.
- Define $\delta_s = \alpha_m{}^\frown\delta_s(m) = \alpha_m{}^\frown f$. Initialize all nodes $\alpha \geq \delta_s$ (i.e., $\alpha >_L \delta_s$ or $\alpha \supseteq \delta_s$). Also initialize all nodes of length $\geq s+1$.
- End Stage s and go to next stage.

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

(2) Otherwise, there are two possible subcases:
   (i) if $\Phi_{j(\alpha_m)}^{C_{e(\alpha_m)}}(j(\alpha_m))[s]$ diverges or it converges but not believable at current stage, let the $C_{e(\alpha_m)}$-restraint $r(\alpha_m, s) = 0$.
   (ii) otherwise, it is a believable computation already convergent at last non α_m-expansionary stage s^-, let the $C_{e(\alpha_m)}$-restraint $r(\alpha_m, s) = r(\alpha_m, s^-)$.

   In both subcases, initialize all nodes $\alpha >_L \alpha_m{}^\frown f$. Go to substage $m+1$ of current stage s if $m+1 < s$.

Case 2. If s is an α_m-expansionary stage, check whether there was a last α_m-expansionary stage s^- such that α_m has not been initialized since then.

(1) If such a last α_m-expansionary stage s^- did not exist, then s is the first α_m-expansionary stage after last initialization. Act as in the basic α_m-strategy.
- Choose a large new witness $w_{\alpha_m,s}$ and a set of fresh *trigger* elements $\{x^k_{\alpha_m,s} : 1 \le k \le q_{\alpha_m} = 2^{3^{|\alpha_m|+1}}\}$ for higher priority β-strategies of length odd with $\beta \le \alpha_m$ (i.e., $\beta <_L \alpha_m$ or $\beta \subseteq \alpha_m$) on the priority tree T to enumerate into $C_{e(\beta)}$ later such that

$$N_{\alpha_m,s} < x^1_{\alpha_m,s} < x^2_{\alpha_m,s} < \ldots < x^{q_{\alpha_m}}_{\alpha_m,s} < w_{\alpha_m,s},$$

  where $N_{\alpha_m,s}$ is a new number larger than all used numbers before; particularly, $N_{\alpha_m,s}$ is bigger than all restraints $r(\beta, s)$ appointed on $C_{e(\beta)}$ by $\mathcal{R}$-strategies β with priority strictly higher than α_m.
- Enumerate the witness $w_{\alpha_m,s}$ into $C_{e(\alpha_m),s}$.
- Define $\delta_s = \alpha_m{}^\frown\delta_s(m) = \alpha_m{}^\frown d$. Initialize all nodes $\alpha \ge \alpha_m{}^\frown d$ and all nodes of length $\ge s+1$.
- End Stage s and go to next stage.

The witness $w_{\alpha_m,s}$ and the triggers $x^k_{\alpha_m,s}(1 \le k \le q_{\alpha_m})$ keep unchanged at later stages unless the node α_m is initialized by higher priority strategies.

(2) If such a last α_m-expansionary stage s^- did exist, then there was a largest α_m-expansionary stage $s_0 \le s^- < s$ such that the witness w_{α_m,s_0} and trigger elements $x^k_{\alpha_m,s_0}$ with $1 \le k \le q_{\alpha_m} = 2^{3^{|\alpha_m|+1}}$ were defined at stage s_0 and α_m has not been initialized since then. Define the current outcome $\delta_s(m)$ of the α_m-strategy started at stage s_0 according to the current state of the strategy.
- If the α_m-strategy waits at Step (2) or at Step (4.n) for some $n \ge 1$, let $\delta_s(m) = d$.
  * Initialize all nodes $\alpha >_L \alpha_m{}^\frown\delta_s(m) = \alpha_m{}^\frown d$. Go to substage $m+1$ of current stage s if $m+1 < s$.
- If the α_m-strategy currently arrives at Step (2), let $\delta_s(m) = d$. Act as in Step (3).
  * Let $t_0 = s$ and $u_{\alpha_m,t_0} = w_{\alpha_m,s} = w_{\alpha_m,s_0}$. Let $y_{\alpha_m,s}$ be the unique even number such that

$$\varphi^2_{i(\alpha_m)}(y_{\alpha_m,s}, l(i(\alpha_m), s)) = w_{\alpha_m,s} = w_{\alpha_m,s_0} \in O_{i(\alpha_m),s} = C_{e(\alpha_m),s}.$$

  The even number $y_{\alpha_m,s}$ remains the same at later stages as long as α_m is not initialized.

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

* Pick the largest trigger element $x^k_{\alpha_m,s} = x^k_{\alpha_m,s_0} < w_{\alpha_m,s_0}$ that has not been enumerated into $C_{e(\beta)}$ by β-strategies with $\beta < \alpha_m$ (i.e., $\beta <_L \alpha_m$ or $\beta \subset \alpha_m$).
* Enumerate $x^k_{\alpha_m,s}$ into $C_{e(\alpha_m),s}$. Go to Step (4.1).*By Lemma 1 below, such a trigger $x^k_{\alpha_m,s_0}$ always exists.*
* Define $\delta_s = \alpha_m{}^\frown\delta_s(m) = \alpha_m{}^\frown d$. Initialize all nodes $\alpha \geq \alpha_m{}^\frown d$ and all nodes of length $\geq s+1$.
* End Stage s and go to next stage.

• If the α_m-strategy arrives at Step $(4.n)$ for some $n \geq 1$, let $\delta_s(m) = \infty$. Act as in Step $(5.n)$.

* Let $t_n = s$ and $u_{\alpha_m,t_n} = \varphi^2_{i(\alpha_m)}(y_{\alpha_m,t_0}, l(i(\alpha_m), s))$. Then we have

$$\begin{aligned} w_{\alpha_m,s_0} \leq u_{\alpha_m,t_{n-1}} &= \varphi^2_{i(\alpha_m)}(y_{\alpha_m,t_0}, l(i(\alpha_m), t_{n-1})) \\ &< \varphi^2_{i(\alpha_m)}(y_{\alpha_m,t_0}, l(i(\alpha_m), t_n)) = u_{\alpha_m,t_n} \in C_{e(\alpha_m),t_n} \end{aligned}$$

because the enumeration of the trigger element $x^k_{\alpha_m,t_0} < w_{\alpha_m,s_0}$ in Step (3) for $n = 1$ or $x^k_{\beta,t} \in (w_{\alpha_m,s_0}, u_{\alpha_m,t_{n-1}})$ in Step (5. $(n-1)$) for $n \geq 2$ forces the number of predecessors of y_{α_m,t_0} computed by $\varphi^2_{i(\alpha_m)}$ to move up.

As $u_{\alpha_m,t_n} \in C_{e(\alpha_m),t_n}$ and $u_{\alpha_m,t_n} > w_{\alpha_m,s_0}$, there is a unique node $\beta > \alpha_m$ on the priority tree T with $e(\beta) = e(\alpha_m)$ such that

$$u_{\alpha_m,t_n} = w_{\beta,t} \text{ or } u_{\alpha_m,t_n} = x^k_{\beta,t} \text{ for some } k,$$

where $w_{\beta,t}$ and $x^k_{\beta,t} (1 \leq k \leq q_\beta = 2^{3^{|\beta|+1}})$ were first appointed on β at some β-stage $t \in (s_0, t_n)$.

* Pick the largest trigger number $x^k_{\beta,t} < u_{\alpha_m,t_n} \leq w_{\beta,t}$ that has not been enumerated into $C_{e(\beta')}$ for any $\beta' \leq \beta$.
* Enumerate $x^k_{\beta,t}$ into $C_{e(\alpha_m),t_n}$. Go to Step $(4.(n+1))$.*By Lemma 1 below, such a trigger $x^k_{\beta,t}$ always exists.*
* Initialize all nodes $\alpha >_L \alpha_m{}^\frown\infty$. Go to substage $m+1$ of current stage s if $m+1 < s$.

This ends the construction.

LEMMA 1. *For each node $\alpha \in T$, let $q_\alpha = 2^{3^{|\alpha|+1}}$. Suppose that s_0 is a first α-stage after last initialization during the construction such that the witness w_{α,s_0} and the set of trigger elements $X_{\alpha,s_0} = \{x^k_{\alpha,s_0} : 1 \leq k \leq q_\alpha\}$ were first chosen at stage s_0. Then there are enough trigger elements from X_{α,s_0} for higher priority β-strategies to enumerate into $C_{e(\beta)}$ after stage s_0. That is,*

$$\{x^k_{\alpha,s_0} \in C_{e(\beta)} : \beta \in T, \beta \leq \alpha, 1 \leq k \leq q_\alpha\} \subsetneq X_{\alpha,s_0}.$$

PROOF. During the construction, only higher priority $\mathcal{R}$-strategies $\beta \leq \alpha$ with $e(\beta) = e(\alpha)$ can enumerate triggers from X_{α,s_0} into $C_{e(\beta)}$ after stage s_0. Furthermore, if $\beta \leq \alpha$ is initialized at some stage $s > s_0$, then it will initiate a new strategy later; thus β will not use triggers from X_{α,s_0} after stage s.

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

Let β_1 be the first $\mathcal{R}$-strategy with $\beta_1 \leq \alpha$ that acts as in Step (3) or Step (5.n) for some n to enumerate a trigger x^k_{α,s_0} into $C_{e(\beta_1),s_1}$ at some stage $s_1 > s_0$. Then there is a unique even number y_{β_1,s_1} such that

$$\varphi^2_{i(\beta_1)}(y_{\beta_1,s_1}, l(i(\beta_1), s_1)) = w_{\alpha,s_0} \in O_{i(\beta_1),s_1} = C_{e(\beta_1),s_1},$$

so we have $e(\beta_1) = e(\alpha)$, and the β_1-strategy enumerates the largest $x^{q_\alpha}_{\alpha,s_0}$ into $C_{e(\beta_1),s_1} = C_{e(\alpha),s_1}$. This enumeration forces the number of predecessors of y_{β_1,s_1} approximated by $\varphi^2_{i(\beta_1)}$ to move up if the β_1-strategy next arrives at Step (4.1) from Step (3) or at Step (4.$(n+1)$) from Step (5.n) at some stage $s > s_1$. That is, at stage s, we have

$$w_{\alpha,s_0} = \varphi^2_{i(\beta_1)}(y_{\beta_1,s_1}, l(i(\beta_1), s_1)) < \varphi^2_{i(\beta_1)}(y_{\beta_1,s_1}, l(i(\beta_1), s)) \in C_{e(\alpha),s}.$$

Since we only enumerate witnesses and triggers of nodes of T into $C_{e(\alpha)}$ during the construction, $\varphi^2_{i(\beta_1)}(y_{\beta_1,s_1}, l(i(\beta_1), s))$ is a trigger or witness of some node $\beta \in T$ with priority strictly lower than α. The β_1-strategy enumerates some trigger of β into $C_{e(\beta_1)} = C_{e(\alpha)}$ at stage s. From this analysis, we see that β_1 never enumerates triggers from the set X_{α,s_0} into $C_{e(\beta_1)}$ after stage s_1. So β_1 uses at most one trigger from X_{α,s_0}.

Let β_2 be the first $\mathcal{R}$-strategy in $\{\beta \in T : \beta \leq \alpha\} \setminus \{\beta_1\}$ that acts as in Step (3) or Step (5.n) for some n to enumerate a trigger x^k_{α,s_0} into $C_{e(\beta_2),s_2}$ at some stage $s_2 > s_1$. Then there is a unique even number y_{β_2,s_2} such that

$$\varphi^2_{i(\beta_2)}(y_{\beta_2,s_2}, l(i(\beta_2), s_2)) = w_{\alpha,s_0} \text{ or } x^{q_\alpha}_{\alpha,s_0} \in O_{i(\beta_2),s_2} = C_{e(\beta_2),s_2},$$

then $e(\beta_2) = e(\alpha)$ and $k = q_\alpha - 1$.

(i) If $\varphi^2_{i(\beta_2)}(y_{\beta_2,s_2}, l(i(\beta_2), s_2)) = w_{\alpha,s_0}$, as in the case of β_1-strategy above, β_2 never enumerates triggers from X_{α,s_0} into $C_{e(\beta_2)}$ after stage s_2.

(ii) If $\varphi^2_{i(\beta_2)}(y_{\beta_2,s_2}, l(i(\beta_2), s_2)) = x^{q_\alpha}_{\alpha,s_0} < w_{\alpha,s_0}$, the enumeration of $x^{q_\alpha - 1}_{\alpha,s_0}$ forces $\varphi^2_{i(\beta_2)}(y_{\beta_2,s_2}, l(i(\beta_2), s)) > x^{q_\alpha}_{\alpha,s_0}$ if the β_2-strategy acts as in Step (5.m) for some m to enumerate triggers at some least stage $s > s_2$.
- If $\varphi^2_{i(\beta_2)}(y_{\beta_2,s_2}, l(i(\beta_2), s)) > w_{\alpha,s_0}$, then β_2 acts to enumerate a trigger of node β with $\beta > \alpha$ at stage s.
- If $\varphi^2_{i(\beta_2)}(y_{\beta_2,s_2}, l(i(\beta_2), s)) = w_{\alpha,s_0}$, then β_2 acts to enumerate the largest unused trigger x^k_{α,s_0} at stage s.

Therefore, the β_2-strategy requires at most two triggers from X_{α,s_0} into $C_{e(\beta_2)}$ after stage s_0.

Let β_3 be the first $\mathcal{R}$-strategy in $\{\beta \in T : \beta \leq \alpha\} \setminus \{\beta_1, \beta_2\}$ that acts as in Step (3) or Step (5.n) for some n to enumerate a trigger x^k_{α,s_0} into $C_{e(\beta_3),s_3}$ at some stage $s_3 > s_2$. Then there is a unique even number y_{β_3,s_3} such that

$$\varphi^2_{i(\beta_3)}(y_{\beta_3,s_3}, l(i(\beta_3), s_3)) = w_{\alpha,s_0} \text{ or } x^k_{\alpha,s_0} \in O_{i(\beta_3),s_3} = C_{e(\beta_3),s_3} = C_{e(\alpha),s_3},$$

and there are at most 1+2=3 triggers $x^k_{\alpha,s_0} \in C_{e(\alpha),s_3}$. Now it requires at most 4 enumerations of new triggers from X_{α,s_0} into $C_{e(\beta_3)} = C_{e(\alpha)}$ to force the number of predecessors of y_{β_3,s_3} approximated by $\varphi^2_{i(\beta_3)}$, namely, $\varphi^2_{i(\beta_3)}(y_{\beta_3,s_3}, \cdot)$, to exceed

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

w_{α,s_0}. The total number of triggers from X_{α,s_0} used by β_1, β_2 and β_3 is at most $1 + 2 + 2^2 = 2^3 - 1$.

Generally, for $m \geq 2$, suppose that β_m is the first $\mathcal{R}$-strategy in $\{\beta \in T : \beta \leq \alpha\} \setminus \{\beta_1, \ldots, \beta_{m-1}\}$ that acts as in Step (3) or Step (5.n) for some n to enumerate a trigger x^k_{α,s_0} into $C_{e(\beta_m),s_m}$ at some stage $s_m > s_{m-1}$. Then there is a unique even number y_{β_m,s_m} such that

$$\varphi^2_{i(\beta_m)}(y_{\beta_m,s_m}, l(i(\beta_m), s_m)) = w_{\alpha,s_0} \text{ or } x^k_{\alpha,s_0} \in O_{i(\beta_m),s_m} = C_{e(\beta_m),s_m} = C_{e(\alpha),s_m},$$

and there are at most $1 + 2 + \ldots + 2^{m-2} = 2^{m-1} - 1$ triggers $x^k_{\alpha,s_0} \in C_{e(\alpha),s_m}$. Since the value of $\varphi^2_{i(\beta_m)}(y_{\beta_m,s_m}, l(i(\beta_m), s_m))$ has at most 2^{m-1} many possible choices, it requires at most 2^{m-1} many enumerations of new triggers from X_{α,s_0} into $C_{e(\beta_m)} = C_{e(\alpha)}$ to force the number of predecessors of y_{β_m,s_m} to exceed w_{α,s_0}. So the total number of triggers from X_{α,s_0} used by $\beta_1, \ldots, \beta_m$ is at most $1 + 2 + \ldots + 2^{m-1} = 2^m - 1$.

Since the number of nodes of length $\leq |\alpha|$ in the priority tree T is strictly less than

$$1 + 3 + \ldots + 3^{|\alpha|} = \frac{3^{|\alpha|+1} - 1}{2} < 3^{|\alpha|+1},$$

the number of higher priority nodes $\beta \in T$ with $\beta \leq \alpha$ is strictly less than $3^{|\alpha|+1}$, and we have $m < 3^{|\alpha|+1}$. This implies that the total number of triggers from X_{α,s_0} used by all higher priority $\mathcal{R}$-strategies β with $\beta \leq \alpha$ is strictly less than

$$1 + 2 + \ldots + 2^{3^{|\alpha|+1}-1} = 2^{3^{|\alpha|+1}} - 1 < 2^{3^{|\alpha|+1}} = q_\alpha.$$

Therefore, we appoint enough trigger elements x^k_{α,s_0} on node α for higher priority β-strategies to enumerate into $C_{e(\beta)} = C_{e(\alpha)}$ during the construction. That is, the trigger elements in Step (3) or Step (5.n) of a basic α-strategy initiated at stage s_0 always exist if needed. This completes the proof of the lemma. ⊣

Let $\mathrm{TP} = \liminf_s \delta_s$ be the leftmost path on T visited infinitely often during the construction, called the *true path* of the construction. That is, for any $n \geq 1$, the node $\mathrm{TP} \upharpoonright_n = \mathrm{TP}(0) \ldots \mathrm{TP}(n-1) \in T$ is visited infinitely often, but any node $\alpha <_L \mathrm{TP} \upharpoonright_n$ is visited finitely often during the construction.

LEMMA 2. TP *is an infinite path on the priority tree* T.

PROOF. The empty node $\lambda \subset \mathrm{TP}$ because every stage is a λ-stage; furthermore, λ has the highest priority on the priority tree T, it is not initialized at stages $s > 0$. Let $\alpha \subset \mathrm{TP}$ with $|\alpha| \geq 0$. Assume that there is a least stage s_α such that α is not initialized at any stage $s > s_\alpha$. There are two cases.

Case 1. If $|\alpha|$ is even, α is a $\mathcal{P}$-strategy. Let t_α be the first α-stage $> s_\alpha$. The α-strategy picks a new witness w_{α,t_α} and a finite set $\{x^k_{\alpha,t_\alpha} : 1 \leq k \leq q_\alpha = 2^{3^{|\alpha|+1}}\}$ of new triggers at stage t_α. Since α has the highest priority after stage s_α, the witness w_{α,t_α} and the triggers x^k_{α,t_α} are never redefined later.

(1) If the α-strategy waits at Step (2) forever after stage t_α, then any α-stage $s \geq t_\alpha$ is an $\alpha^\frown f$-stage. In this case, $\alpha^\frown f$ is not initialized after stage t_α, α has true outcome f, and we have $\alpha^\frown f \subset \mathrm{TP}$.

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

(2) Otherwise, the α-strategy arrives at Step (2) and acts as in Step (3) at some stage $s > t_\alpha$; the strategy enumerates the witness w_{α,t_α} into $C_{e(\alpha),s}$, making $C_{e(\alpha)} \neq \varphi_{i(\alpha)}$, and the construction is terminated at stage s with the current true path $\delta_s = \alpha^\frown d$. Then any α-stage $s' \geq s$ is an $\alpha^\frown d$-stage, and $\alpha^\frown d$ is not initialized after stage s. So we have $\alpha^\frown d \subset \mathrm{TP}$.

Case 2. If $|\alpha|$ is odd, then α is an $\mathcal{R}$-strategy. There are two subcases.

(1) If there are finitely many α-expansionary stages, let t_α be the least stage $> s_\alpha$ such that any $s \geq t_\alpha$ is not an α-expansionary stage. The basic α-strategy acts at most once to appoint a new restraint on $C_{e(\alpha)}$ at some stage $s \geq t_\alpha$ if the believable computation $\Phi_{j(\alpha)}^{C_{e(\alpha)}}(j(\alpha))[s]$ newly converges in which case the α-strategy terminates current construction by setting the current true path $\delta_s = \alpha^\frown f$ and initializing all nodes $\geq \alpha^\frown f$. This action preserves the believable computation $\Phi_{j(\alpha)}^{C_{e(\alpha)}}(j(\alpha))[s]$ forever, and the α-strategy never sets new $C_{e(\alpha)}$-restraints later. Then $\alpha^\frown f$ is not initialized after stage s and any α-stage $s' \geq s$ is an $\alpha^\frown f$-stage. So we have $\alpha^\frown f \subset \mathrm{TP}$.

(2) If there are infinitely many α-expansionary stages, let t_α be the first α-expansionary stage $> s_\alpha$. The α-strategy picks a new witness w_{α,t_α} and a finite set $\{x_{\alpha,t_\alpha}^k : 1 \leq k \leq q_\alpha = 2^{3^{|\alpha|+1}}\}$ of new triggers, it first enumerates w_{α,t_α} into $C_{e(\alpha),t_\alpha}$ at the same stage t_α. Since α has the highest priority after stage s_α, the witness w_{α,t_α} and the triggers x_{α,t_α}^k are never redefined later.

- If the α-strategy waits at Step (2) forever after stage t_α, then any α-expansionary stage $s \geq t_\alpha$ is an $\alpha^\frown d$-stage. In this case, $\alpha^\frown d$ is not initialized after stage t_α, and we have $\alpha^\frown d \subset \mathrm{TP}$.
- Otherwise, the α-strategy arrives at Step (2) and acts as in Step (3) at some stage $t_0 > t_\alpha$. At stage t_0, the strategy enumerates the largest unused trigger x_{α,t_α}^k into $C_{e(\alpha),t_0}$; the construction is terminated by setting the current true path $\delta_{t_0} = \alpha^\frown d$, and initializing all nodes $\geq \alpha^\frown d$. There are two possible situations after stage t_0.
  - The α-strategy waits at Step $(4.n)$ forever after certain stage $s > t_0$. Then any α-expansionary stage $s' \geq s$ is an $\alpha^\frown d$-stage. In this case, $\alpha^\frown d$ is not initialized after stage s and $\alpha^\frown d \subset \mathrm{TP}$.
  - The α-strategy arrives at Step $(4.(n+1))$ from Step $(5.n)$ infinitely often after stage t_0. Then there are infinitely many α-expansionary stages $s > t_0$ such that the α-strategy acts as in Step $(5.n)$ for some n at stage s by enumerating a largest unused trigger of some node with lower priority into $C_{e(\alpha),s}$. Such a stage s is an $\alpha^\frown\infty$-stage. In this case, $\alpha^\frown\infty$ is not initialized after stage t_0 and $\alpha^\frown\infty \subset \mathrm{TP}$.

We have seen that for any $\alpha \subset \mathrm{TP}$ with $|\alpha| \geq 0$, there is a least stage s_α such that α is not initialized after stage s_α. The α-strategy acts after stage s_α with an outcome o such that $\alpha^\frown o \subset \mathrm{TP}$. This shows that TP is an infinite path on the priority tree T. ⊣

LEMMA 3. *For all e, C_e is noncomputable.*

PROOF. For fixed numbers e, i, let α be the unique $\mathcal{P}_{\langle e,i\rangle}$-strategy along the true path TP of the construction, then α is initialized finitely often, and there are infinitely

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

many α-stages during the construction. Suppose that α has the highest priority after some least stage s_α. The α-strategy acts to diagonalize against φ_i computing C_e after stage s_α.

(i) If the strategy waits at Step (2) forever after certain stage, then there is a witness w such that either $\varphi_i(w)$ diverges or it converges with $\varphi_i(w)\downarrow = 1 \neq C_e(w) = 0$; in this case, α has true outcome f.
(ii) If the strategy arrives at Step (2) and acts as in Step (3) at some stage $s > s_\alpha$, then there is a witness w such that $\varphi_i(w)\downarrow = 0 \neq C_e(w) = 1$; in this case, α has true outcome d.

The α-strategy succeeds to ensure that $C_e \neq \varphi_i$ after stage s_α. Then $C_e \neq \varphi_i$ for all i, and thus it is not computable.

LEMMA 4. *For all e, $e \in \mathrm{Cof}^K$ if and only if C_e is order-computable.*

PROOF. Fix a number e. If $e \in \mathrm{Cof}^K$, W_e^K is cofinite. Then there exists a number i such that $[i, \infty) \subseteq W_e^K$, that is, $[i, i+j+1] \subseteq W_e^K$ for all j. For any node α assigned an $\mathcal{R}_{\langle e,i,\cdot\rangle}$-requirement on the priority tree, there are only finitely many α-expansionary stages. For each j, there is a unique node $\alpha_{\langle e,i,j\rangle}$ working for $\mathcal{R}_{\langle e,i,j\rangle}$ along the true path TP of the construction such that

$$\alpha_{\langle e,i,0\rangle}{}^\frown f \subset \alpha_{\langle e,i,1\rangle}{}^\frown f \subset \ldots \subset \alpha_{\langle e,i,j\rangle}{}^\frown f \subset \ldots \subset \mathrm{TP}.$$

For each j, the $\alpha_{\langle e,i,j\rangle}$-strategy is not initialized after certain stage s_j. Then $s_0 \leq s_1 \leq \ldots \leq s_j \leq \ldots$ because of the priority of the strategies. $\alpha_{\langle e,i,j\rangle}$ acts at most once to appoint a new C_e-restraint $\phi_j^{C_e}(j)[s]$ to preserve the believable computation $\Phi_j^{C_e}(j)[s]$ if it newly converges at some stage $s \in (s_j, s_{j+1}]$. Since the computation $\Phi_j^{C_e}(j)[s]\downarrow$ is believable, all higher priority $\mathcal{R}$-strategies β with $\beta{}^\frown\infty \subset \alpha_{\langle e,i,j\rangle}$ only enumerate triggers $x^k_{\beta',s'}$ of nodes $\beta' > \alpha_{\langle e,i,j\rangle}$ at any stage $s' \geq s$ such that $x^1_{\beta',s'} > \phi_j^{C_e}(j)[s]$, the use of the believable computation. Then the computation $\Phi_j^{C_e}(j)[s]\downarrow$ is not injured by β-strategy after stage s, and thus, it is preserved forever. Then C_e' is a Δ_2^0 set because for all j, $j \in C_e'$ if and only $\Phi_j^{C_e}(j)$ converges if and only if there are infinitely many stages s such that the computation $\Phi_j^{C_e}(j)[s]\downarrow$ is believable. Therefore, C_e is a low c.e. set, and thus, it is order-computable.

If $e \notin \mathrm{Cof}^K$, W_e^K is not cofinite. Now for all i, there is a least number j_i such that $[i, i+j_i+1] \nsubseteq W_e^K$. For all i, there are only finitely many nodes for $\mathcal{R}_{\langle e,i,\cdot\rangle}$-requirements along the true path TP of the construction, one node $\alpha_{\langle e,i,j\rangle}$ for $\mathcal{R}_{\langle e,i,j\rangle}$ with $0 \leq j \leq j_i$ such that each $\alpha_{\langle e,i,j\rangle}$ with $j < j_i$ has the finite outcome f and the longest node $\alpha_{\langle e,i,j_i\rangle}$ has an infinite outcome $o \in \{d, \infty\}$. That is,

$$\alpha_{\langle e,i,0\rangle}{}^\frown f \subset \alpha_{\langle e,i,1\rangle}{}^\frown f \subset \ldots \subset \alpha_{\langle e,i,j_i-1\rangle}{}^\frown f \subset \alpha_{\langle e,i,j_i\rangle}{}^\frown o \subset \mathrm{TP}.$$

Let $\alpha = \alpha_{\langle e,i,j_i\rangle}$ be the $\mathcal{R}_{\langle e,i,j_i\rangle}$-strategy along the true path TP of the construction, then α is initialized finitely often, and there are infinitely many α-expansionary stages. α has the highest priority after certain stage s_α. After stage s_α, the α-strategy acts to diagonalize against φ_i^2 to be a computable predecessor approximation function for C_e.

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

(i) If the strategy waits at Step (2) or Step $(4.n)$ forever after certain stage, then either $\lim_s l(i,s) < \infty$ or $C_e \neq O_i$, the order-computable set computed by φ_i^2; in this case, α has true outcome d, and $\alpha^\frown d \subset \mathrm{TP}$.
(ii) If the strategy first arrives at Step (2) and then arrives at Step $(4.(n+1))$ from Step $(5.n)$ infinitely often, then there is an even number y such that $\lim_s \varphi_i^2(y,s) = \infty$; in this case, α has true outcome ∞, and $\alpha^\frown\infty \subset \mathrm{TP}$.

The α-strategy succeeds in ensuring that C_e is not order-computed by φ_i^2 after stage s_α. Then C_e is not order-computed by φ_i^2 for all i, and thus it is not order-computable. ⊣

We have constructed a uniform sequence of c.e. sets $\langle C_e : e \in \mathbb{N}\rangle$ such that $e \in \mathrm{Cof}^K$ if and only if C_e is order-computable for all e. Since Cof^K is Σ_4^0-complete, so is the index set of c.e. order-computable sets. This completes the proof of Theorem 1. ⊣

Recall that $\mathcal{I} = \{e \in \mathbb{N} : \varphi_e^2$ is total, and $(\forall x)[\lim_s \varphi_e^2(x,s) \downarrow \in \{0,1\}]\}$ is the index set of Δ_2^0 sets. For $e \in \mathcal{I}$, $A_e = \{x \in \mathbb{N} : (\forall x)[\lim_s \varphi_e^2(x,s) \downarrow = 1]\}$ is the Δ_2^0 set with index e. Since both c.e. sets and order-computable sets form subclasses of Δ_2^0 sets, based on Theorem 1, we obtain the exact complexity for general order-computable sets.

COROLLARY 1. *The index set* $\{e \in \mathcal{I} : A_e$ *is order-computable*$\}$ *is* Σ_4^0*-complete within* $\mathcal{I}$.

PROOF. For a number e, $e \in \mathcal{I}$ if and only if φ_e^2 is a computable binary function such that $\lim_s \varphi_e^2(x,s)$ converges to 0 or 1 for all x. To prove the corollary, it suffices to construct a uniform sequence $\langle F_e : e \in \mathbb{N}\rangle$ of computable binary functions such that the following two conditions hold:

(1) for all e, $\lim_s F_e(x,s)$ converges to 0 or 1 for all x;
(2) for all e, $e \in \mathrm{Cof}^K \Leftrightarrow B_e = \{x \in \mathbb{N} : \lim_s F_e(x,s) \downarrow = 1\}$ is order-computable.

Let $\langle C_e : e \in \mathbb{N}\rangle$ be the uniform sequence of c.e. sets constructed in Theorem 1 such that $e \in \mathrm{Cof}^K \Leftrightarrow C_e$ is order-computable for all e. For any e, x, s and $t > x, s$, define $F_{e,t}(x,s) = C_{e,s}(x)$. Then the sequence $\langle F_e : e \in \mathbb{N}\rangle$ meets the desired conditions above. First, $F_e(x,s)$ is defined for all x, s, so F_e is a computable binary function. Second, since $C_{e,s}(x)$ changes from 0 to 1 for at most once when x is first enumerated into C_e at stage s, the condition (1) holds. Third, $\lim_s F_e(x,s)$ converges to 1 if and only if $x \in C_e$, so $B_e = \{x \in \mathbb{N} : \lim_s F_e(x,s) \downarrow = 1\} = C_e$ for all e; the condition (2) holds. ⊣

§4. Index set of Δ_2^0 sets. We continue to study the complexity of the index set $\mathcal{I}$ of Δ_2^0 sets.

THEOREM 2. *The index set* $\mathcal{I}$ *of* Δ_2^0 *sets is* Π_3^0*-complete.*

PROOF. For any number e, e is an index of a Δ_2^0 set if and only if φ_e^2 is total and $\lim_s \varphi_e^2(x,s)$ converges to 0 or 1 for all x in which case e is the index of the Δ_2^0 set $A_e = \{x \in \mathbb{N} : \lim_s \varphi_e^2(x,s) \downarrow = 1\}$. As $\mathrm{Tot}^K = \{e \in \mathbb{N} : (\forall x)[\Phi_e^K(x)$ converges$]\}$ is Π_2^0-complete relative the c.e. complete set K, it is Π_3^0-complete. To prove the theorem, it

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

suffices to construct a uniform sequence $\langle F_e : e \in \mathbb{N}\rangle$ of computable binary functions such that for all e,

$$e \in \mathrm{Tot}^K \Leftrightarrow (\forall x)[\lim_s F_e(x,s) \downarrow = 0 \text{ or } 1].$$

We will build a computable ternary function $F(\cdot,\cdot,\cdot)$ satisfying the following requirements:

$\mathcal{R}_{\langle e,x\rangle}$: If $\Phi_e^K(x)$ is defined, then $\lim_s F(e,x,s)$ converges to 0.
If $\Phi_e^K(x)$ is undefined, then $\lim_s F(e,x,s)$ diverges.

Then $\langle F_e = F(e,\cdot,\cdot) : e \in \mathbb{N}\rangle$ is the desired sequence of computable binary functions.

If $e \in \mathrm{Tot}^K$, Φ_e^K is total, i.e., $\Phi_e^K(x)$ is defined for all x, then $\mathcal{R}_{\langle e,x\rangle}$ ensures that $\lim_s F_e(x,s)$ converges to 0. In this case, F_e approximates the empty set $\emptyset = \{x : \lim_s F_e(x,s) \downarrow = 1\}$. If $e \notin \mathrm{Tot}^K$, Φ_e^K is not total, i.e., there is a number x such that $\Phi_e^K(x)$ is undefined, then $\mathcal{R}_{\langle e,x\rangle}$ ensures that $\lim_s F(e,x,s)$ diverges. In this case, F_e cannot approximate a Δ_2^0 set.

Fix an effective bijection $\langle\cdot,\cdot\rangle : \mathbb{N}^2 \to \mathbb{N}$, and for all i,j,k, let $\langle i,j,k\rangle = \langle\langle i,j\rangle,k\rangle$. We construct the computable ternary function $F(\cdot,\cdot,\cdot)$ by stages.

Construction.

Stage 0. Define $F(0,0,0) = F(0,0,1) = 0$.

Assume that we have defined $F(e,x,y)$ for all e,x with $e,x \le s-1$ and $y \le 2s-1$ by the end of stage $s-1$.

Stage $s \ge 1$. For all $e,x \le s$, define $F(e,x,\cdot)$ as follows:

Step 1. For all $e,x < s$, define $F(e,x,2s)$ and $F(e,x,2s+1)$ as follows. There are two cases:

(1) If there was a last stage $s^- < s$ such that $\Phi_e^K(x)[s^-]$ was defined with use $\phi_e^K(x)[s^-]$ and the computation has not been changed since then, that is, $\Phi_e^K(x)[s]$ is defined with use $\phi_e^K(x)[s] = \phi_e^K(x)[s^-]$, define

$$F(e,x,2s) = F(e,x,2s+1) = 0.$$

(2) Otherwise, either $\Phi_e^K(x)[t]$ was undefined for all $t < s$, or there was a convergent computation $\Phi_e^K(x)[s^-]$ at last stage $s^- < s$ but the computation is changed currently, that is, either $\Phi_e^K(x)[s]$ is undefined or it is defined with use $\phi_e^K(x)[s] > \phi_e^K(x)[s^-]$, define

$$F(e,x,2s) = 0 \text{ and } F(e,x,2s+1) = 1.$$

Step 2. For all $e,x \le s$ and $t \le 2s+1$, define $F(e,s,t) = F(s,x,t) = 0$.

This ends the construction.

For all $e,x \in \mathbb{N}$, at any stage s bigger than e,x of the construction, we have defined $F(e,x,y)$ for all $y \le 2s+1$ by the end of stage s. Furthermore, the value of $F(e,x,y)$ is never changed during the construction. So F is a computable ternary function.

LEMMA 5. *For all* $e,x \in \mathbb{N}$, $\mathcal{R}_{\langle e,x\rangle}$ *is satisfied.*

PROOF. Fix numbers e,x. If $\Phi_e^K(x)$ is defined, then there is a least stage s such that the $\Phi_e^K(x)[s]$ is defined with use $\phi_e^K(x)[s]$ and the computation is not changed later;

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

that is, at any stage $t \geq s$, the computation $\Phi_e^K(x)[t]$ is defined with use $\phi_e^K(x)[t]$ the same as $\phi_e^K(x)[s]$. Let $s_{e,x}$ be such a least stage bigger than e, x. Then at any stage $s > s_{e,x}$, we always defined $F(e, x, 2s) = F(e, x, 2s + 1) = 0$. So $F(e, x, y) = 0$ for all $y > 2s_{e,x}$ and we have $\lim_s F(e, x, s) = 0$.

If $\Phi_e^K(x)$ is undefined, then there are infinitely many stages $s > e, x$ such that either the computation $\Phi_e^K(x)[s]$ is undefined or it is defined with use strictly bigger than that of the last convergent computation. At such a stage s, we defined $F(e, x, 2s) = 0$, but $F(e, x, 2s + 1) = 1$. So $\lim_s F(e, x, s)$ does not exist. ⊣

For a number e, there are two situations:

- If $e \in \mathrm{Tot}^K$, then $\Phi_e^K(x)$ is defined for all x. By Lemma 5, $\lim_s F(e, x, s) = 0$ for all x. In this case, $F_e = F(e, \cdot, \cdot)$ approximates the Δ_2^0 set $\{x : \lim_s F(e, x, s) \downarrow = 1\}$, which is exactly the empty set $\emptyset$.
- If $e \notin \mathrm{Tot}^K$, then $\Phi_e^K(x)$ is undefined for some x. By Lemma 5, $\lim_s F(e, x, s)$ does not exist for this x. In this case, $F_e = F(e, \cdot, \cdot)$ cannot approximate any Δ_2^0 set.

We have constructed a uniform sequence of computable binary functions $\langle F_e = F(e, \cdot, \cdot) : e \in \mathbb{N}\rangle$ such that for all e, Φ_e^K is total if and only if $\lim_s F_e(x, s)$ exists with limit 0 for all x. So the index set $\mathcal{I}$ of Δ_2^0 sets is Π_3^0-complete.

This completes the proof of Theorem 2. ⊣

Acknowledgments. The author sincerely thanks the referees for the supportive comments and useful suggestions, which have improved the quality of the original paper.

Funding. This work was supported by the National Natural Science Foundation of China (Grant No. 12301001).

REFERENCES

[1] C. J. Ash and J. F. Knight, ***Computable Structures and the Hyperarithmetical Hierarchy***, Studies in Logic and the Foundations of Mathematics, 144, North-Holland Publishing Co., Amsterdam, 2000.

[2] W. Calvert, *The isomorphism problem for classes of computable fields*. ***Archive for Mathematical Logic***, vol. 43 (2004), pp. 327–336.

[3] ———, *The isomorphism problem for computable Abelian p-groups of bounded length*. ***Journal of Symbolic Logic***, vol. 70 (2005), pp. 331–345.

[4] W. Calvert and J. F. Knight, *Classification from a computable viewpoint*. ***The Bulletin of Symbolic Logic***, vol. 12 (2006), pp. 191–218.

[5] C. J. Conidis, *On the complexity of radicals in noncommutative rings*. ***Journal of Algebra***, vol. 322 (2009), pp. 3670–3680.

[6] ———, *The complexity of module radicals*. ***Notre Dame Journal of Formal Logic***, vol. 62 (2021), pp. 353–368.

[7] R. G. Downey and D. R. Hirschfeldt, *Computability theory*, ***Algorithmic Randomness and Complexity***, Theory and Applications of Computability, (L. Bienvenu, P. Bonizzoni, V. Brattka, E. Mayordomo, and P. Panangaden, editors), Springer, New York, NY, 2010, pp. 7–109.

[8] R. G. Downey and A. G. Melnikov, *Effectively categorical abelian groups*. ***Journal of Algebra***, vol. 373 (2013), pp. 223–248.

[9] ———, *Computable completely decomposable groups*. ***Transactions of the American Mathematical Society***, vol. 366 (2014), pp. 4243–4266.

[10] R. G. Downey and A. Montalbán, *The isomorphism problem for torsion-free abelian groups is analytic complete*. ***Journal of Algebra***, vol. 320 (2008), pp. 2291–2300.

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press

[11] V. S. Harizanov, *Pure computable model theory*, ***Handbook of Recursive Mathematics: Recursive Model Theory***, ***vol.*** 1, (Yu. L. Ershov, S. S. Goncharov, A. Nerode, J. B. Remmel, and V. W. Marek, editors), volume 138 of Studies in Logic and the Foundations of Mathematics, North-Holland, Amsterdam, 1998, pp. 3–114.

[12] V. S. Harizanov, S. Lempp, C. F. D. McCoy, A. S. Morozov, and R. Solomon, *On the isomorphism problem for some classes of computable algebraic structures*. ***Archive for Mathematical Logic***, vol. 61 (2022), pp. 813–825.

[13] D. Hirschfeldt, R. Miller, and S. Podzorov, *Order-computable sets*. ***Notre Dame Journal of Formal Logic***, vol. 48 (2007), pp. 317–347.

[14] S. Lempp, *The computational complexity of torsion-freeness of finitely presented groups*. ***Bulletin of the Australian Mathematical Society***, vol. 56 (1997), pp. 273–277.

[15] A. G. Melnikov, *Computable abelian groups*. ***Bulletin of Symbolic Logic***, vol. 20 (2014), pp. 315–356.

[16] A. Nies, ***Computability and Randomness***, Oxford University Press, Inc., New York, 2009.

[17] K. Riggs, *The decomposablity problem for torsion-free abelian groups is analytic-complete*. ***Proceedings of the American Mathmatical Society***, vol. 143 (2015), pp. 3631–3640.

[18] R. I. Soare, ***Recursively Enumerable Sets and Degrees***, Springer-Verlag, Berlin, 1987.

[19] ———, ***Turing Computability***, Springer-Verlag, Berlin, Heidelberg, 2016.

[20] H. Wu, *The complexity of decomposability of computable rings*. ***Notre Dame Journal of Formal Logic***, vol. 64 (2023), pp. 1–14.

SCHOOL OF INFORMATION SCIENCE
BEIJING LANGUAGE AND CULTURE UNIVERSITY
15 XUEYUAN ROAD, HAIDIAN DISTRICT
BEIJING 100083
CHINA
E-mail: huishanwu@blcu.edu.cn

https://doi.org/10.1017/jsl.2025.5 Published online by Cambridge University Press